



INA BRAINGS SALES JAPAN CO.,LTD.



KOYO 46230 tapered roller bearings

Bearing No. 46230

Size	150x225x56 mm
Bore Diameter	150 mm
Outer Diameter	225 mm
Width	56 mm
d	150 mm
D	225 mm
T	56 mm
C	50 mm
r min.	3 mm
r1 min.	1 mm
da min.	164 mm
Da min	213 mm
ra max.	2,5 mm
rb max.	1 mm
Weight	7,09 Kg
Basic dynamic load rating (C)	278 kN
Basic static load rating (C0)	476 kN
(Grease) Lubrication Speed	1200 r/min
(Oil) Lubrication Speed	1600 r/min
Calculation factor (e)	0,33
Calculation factor (Y0)	1,98
Bearing No.	46230
r(min)	3
r1(min)	1
Cr	348
C0r	476

46230 Bearing 2D drawings and 3D CAD models



INA BRAINGS SALES JAPAN CO.,LTD.

Cu	31.6
Grease lub.	1200
Oil lub.	1600
da(min)	164
Da(min)	219
Sa(min)	3
ra(max)	2.5
rb(max)	1
e	0.33
Y2	2.03
Y3	3.02
Y0	1.98
(Refer.)Mass(kg)	7.09