




INA BRAINGS SALES JAPAN CO.,LTD.



6210ZZNR Bearing 2D drawings and 3D CAD models

50,000 mm x 90,000 mm x 20,000 mm NTN
6210ZZNR deep groove ball bearings

Bearing No. 6210ZZNR

Size	50x90x20 mm
Bore Diameter	50,000 mm
Outer Diameter	90,000 mm
Width	20,000 mm
d	50,000 mm
D	90,000 mm
B	20,000 mm
C	20,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359010862
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	50MM Bore; 90MM



INA BRAINGS SALES JAPAN CO.,LTD.

	Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Other Features	Deep Groove With Snap Ring Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	1.0747
Bore	1.969 Inch 50 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
bore diameter:	50 mm
static load capacity:	23200 N
outside diameter:	90 mm
precision rating:	ISO Class 0
overall width:	20 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	20 mm



INA BRAINGS SALES JAPAN CO.,LTD.

snap ring included:	With Snap Ring
outer ring width:	20 mm
internal clearance:	CN
maximum rpm (grease):	7100 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1.1 mm
dynamic load capacity:	35000 N
manufacturer product page:	Click here